

Directions for use:

PHOSfloc

1. With circulation system on, adjust pool water pH to 7.0-7.2 before adding **PHOSfloc- VERY IMPORTANT**
2. Add 4lbs (or required amount) of **PHOSfloc** to a large bucket or water and mix. If your pool has recirculation (filter bypass) setting, add **PHOSfloc**/water mixture slowly to skimmer and allow water to circulate for 1 hour. Do not add directly to filter. Turn system off and allow **PHOSfloc** to settle (this may take up to 12 hours). **VACUUM SEDIMENT TO WASTE** (do NOT vacuum to filter)

OR

If no recirculation (filter bypass) setting is available, add 4lbs of **PHOSfloc** to a large bucket of water and mix. With filter system off, broadcast this mixture over the water while walking around pool. Allow **PHOSfloc** to settle (this may take up to 12 hours). **VACUUM SEDIMENT TO WASTE**. Do NOT vacuum to filter

3. **Important!** It is necessary to further reduce phosphate level to near zero by using **PHOSfree**
4. Continue to maintain near zero phosphate levels all season long with **Pool Perfect+PHOSfree**, for easy weekly maintenance

Important: Always make sure enough PHOSfloc is added to pool versus the amount of water in pool.

(eg: A 20,000 gallon (75,000L) pool must have 2- 4lbs containers of PHOSfloc added). If not enough PHOSfloc is added, the product will not floc properly.